 0,5 mm



Eg



Valnød




Røget Eg




Hvid Eg


 ● 40 x 11 mm

 ● 9 mm

 20 x 600 x 2400 mm (+/- 2 mm)

 13 mm


 1,44 m²

 11,4 kg (+/- 10%)


Passende FJORDWALL tilbehør:

- Montageskruer 4,5 x 45 mm. sort
- Montagelim 290 ml.
- Afslutningslister


Figur 1:



Figur 2:



Frequency [Hz]	α_s
100	0.09
125	0.22
160	0.30
200	0.53
250	0.56
315	0.87
400	0.99
500	1.97
630	0.97
800	1.02
1k	1.02
1.25k	0.91
1.6k	0.90
2k	0.87
2.5k	0.80
3.15k	0.81
4k	0.77
5k	0.71




Lydstest Figur 3:

Montage: afstand 45 mm luft bag panelet.
Lukket ramme omkring kant.

Testareal: 10,8 m²
Rum-volumen: 215 m³
Rum-overflade areal: 305 m²

Frequency [Hz]	α_s
100	0.02
125	0.02
160	0.02
200	0.05
250	0.05
315	0.11
400	0.16
500	0.26
630	0.32
800	0.46
1k	0.63
1.25k	0.78
1.6k	0.97
2k	1.11
2.5k	1.05
3.15k	0.88
4k	0.75
5k	0.68



Lydstest Figur 4:

Montage: De 11 paneler ligger fladt på betongulv i ekkotest-rummet.
Lukket ramme omkring kant.

Testareal: 10,8 m²
Rum-volumen: 215 m³
Rum-overflade areal: 305 m²